

FIXED BIOGAS AND LANDFILL GAS ANALYSER | ANAEROBIC DIGESTION



FIELD-PROVEN GAS ANALYSIS TECHNOLOGY TO OFFER COST-EFFECTIVE ONLINE MONITORING.

The BIOGAS 3000 is our next generation fixed analyzer that offers optimal continuous monitoring of the gas production process, using up to four sample ports to monitor CH₄, CO₂, O₂, H₂S and H₂ levels. The BIOGAS 3000 design builds on previous analyzer strengths and incorporates easy installation with on-site maintenance of all parts, resulting in zero operational downtime for servicing.



FEATURES

- Up to 4 sample points to monitor the complete gas control process
- Monitor before and after desulphurization
- Continuous monitoring Option
- Full Color display
- Calibration to ISO/IEC 17025
- Built-in Liquid level monitoring with dedicated alarm and fault notifications
- IP65 Rated enclosure
- Certified for use in CSA, ATEX and IECeX Zone 2 areas
- Modbus RTU communication
- Optional Profibus and Profinet communication

BENEFITS

- Sample multiple gases simultaneously
- Verify removal of H₂S
- Increased data collection
- Easy-to-Read
- Optimum accuracy
- Precise notification and increased safety
- Highly corrosion resistant
- Use in potentially explosive gas atmospheres (zone 2)
- Remote communication
- More flexible system intergration

*Does not apply to auto calibration section.

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

BIOGAS 3000

APPLICATIONS

- Anaerobic Digestion
- Biogas Monitoring
- Landfill Gas Monitoring

TECHNICAL SPECIFICATIONS


GENERAL SPECIFICATION						
Number of sampling points	1-4					
Gases to be monitored	CH ₄ , CO ₂ and O ₂ with optional H ₂ S, H ₂ and CO (choice of up to 5)					
Reading intervals	User definable, with a continuous ¹ CH ₄ , CO ₂ and O ₂ option available					
Operating temperature range	0°C to +50°C without heater, -20°C to +50°C with heater					
POWER						
Power Supply	110-230 VAC 50/60Hz					
Consumption	155W max.					
Backup Memory	Lithium manganese dioxide backup battery for memory retention					
GAS RANGES						
Gases measured	CH ₄ and CO ₂					
	O ₂					
	H ₂ S/H ₂ /CO					
Standard gas cells	Cell	Range	Typical accuracy(range : accuracy)*			
	CH ₄	0-100%	0-70% : ±0.5% (vol)	70-100% : ±1.5% (vol)		
	CO ₂	0-100%	0-60% : ± 0.5% (vol)	60-100% : ±1.5% (vol)		
Optional gas cell	Cell	Range	Typical accuracy (Range : accuracy)*			
			Internal accuracy	External accuracy		
	H ₂ S	0-50ppm	±1.5% FS	±1.5%FS		
	H ₂ S	0-200ppm	±2.0% FS	±1.5%FS		
	H ₂ S	0-500ppm	±2.0% FS	±2.0% FS		
	H ₂ S	0-1,000ppm	±2.0% FS	±2.0% FS		
	H ₂ S	0-5,000ppm	±2.0% FS	±100ppm or 5% of reading (if greater)		
	H ₂ S	0-10,000ppm	±5.0% FS	±200ppm or 5% of reading (if greater)		
	CO	0-1,000ppm	±2.0% FS	±3.0%FS		
			H ₂	0-1,000ppm	±2.5% FS	±1.5%FS
Response time, T90**			Range	Response time		
	CH ₄	≤10 seconds	H ₂ S (0-50ppm)	≤30 seconds		
	CO ₂	≤10 seconds	H ₂ S (0-200ppm)	≤35 seconds		
	O ₂	≤20 seconds	H ₂ S (0-500ppm)	≤35 seconds		
			H ₂ S (0-1,000ppm)	≤35 seconds		
		H ₂	≤90 seconds	H ₂ S (0-5,000ppm)	≤40 seconds	
	CO	≤30 seconds	H ₂ S (0-10,000ppm)	≤40 seconds		
Cell Lifetime	O ₂ cell is 3 years in air, all other cells 2 years in air					

** Times are taken from the point gas enters the BIOGAS 3000 module. Sample times will vary depending on length of sample pipe

QED Environmental Systems Inc.

2355 Bishop Circle West Dexter, MI 48130, USA

BIOGAS 3000



TECHNICAL SPECIFICATIONS CONTINUED

PUMP	
Flow	300ml / min typically
Flow-fail point	Flow rate less than 75ml/min or vacuum greater than 350mbar
Maximum vacuum restart	
COMMUNICATIONS	
Output channels	Up to six analogue 4-20mA output channels that are user configurable for current sink or source inputs plus Modbus RTU digital output. Optional Profibus module Optional Profinet module Optional Ethernet module
	1 x fault relay 7 x user-configurable alarms that can trigger a relay when above or below a set value. In addition, one can be used to indicate to the operator when the catchpot is full and requires emptying.
Relay outputs	Single pole changeover 6A 24Vdc relay volt free
ENVIRONMENT CONDITIONS	
Operating pressures	350 mbar to +350 mbar
IP rating	IP65
Humidity	0-95% non-condensing humidity
PHYSICAL	
Weight	36.5kg
Size	650 x 600 x 210mm (with supplied wall mounting brackets)
Enclosure	Stainless steel, 600 x 600 x 210mm, IP65 rated
Operation keys	Alpha-numeric keypad with 'tactile' membrane
Display	Ultra-clear high resolution 4.3" full colour TFT
Moisture removal filters	User replaceable microfibre filter and 2.0µm ptfе water traps
Heater option	Optional 100W mains powered ATEX certified heater for 110V or 230V mains supply
CERTIFICATIONS	
ISO 9001	Systems are calibrated in an ISO 9001 Facility (Certificate #: C2024-05506)
ISO/IEC 17025	Systems are Calibrated in an ISO/IEC 17025 Calibration Lab (Certificate #:L24-282)
ATEX / IECEx marking	Ex II 3G Ex nA nC IIA T1 Gc (-20°C ≤ Ta ≤ +50°C)
CSA	Ex nA nC IIA T1 Gc
BS EN 61010-1:2010	Safety requirements for electrical equipment for measurement, control, and laboratory use
BS EN 50270:2006	Electromagnetic compatibility- electrical apparatus for the detection and measurement of combustible gases, toxic gases or oxygen

¹ Continuous option will include a minimum 3 minute daily air purge



*Plus accuracy of calibration gas used

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

Data Sheet Reference : TDS-2384 (Issue 03)

© Product designs and specifications are subject to change without notice. User is responsible for determining suitability of product.

QED Environmental Systems Inc.
2355 Bishop Circle West Dexter, MI 48130, USA



Data Sheet Reference : TDS-2384 (Issue 03)

 info@qedenv.com

 800.624.2026
734.995.2547

WWW.QEDENV.COM

 sales@qedenv.co.uk

 +44 (0) 333 800 0088